

KNOX MEDVAULT® 2.75

SECURE NARCOTICS STORAGE

The Knox MedVault 2.75 family of products (available in two sizes) offers secure narcotics storage designed for first responder vehicle applications. Through networking features, access and entry records are automatically uploaded to KnoxConnect Cloud Management Software, allowing for comprehensive record reviews. In addition, with integrations available to send audit data to inventory systems, MedVault 2.75 can strengthen the chain of customer tracking and reporting.







MedVault 2.75 Mini Surface Mount



MedVault 2.75 Mini Recessed Mount

SECURITY:

Durable cast aluminum construction provide greater protection than sheet metal storage cabinets

DUAL AUTHENTICATION:

Access options include use of single or dual PIN

ACCOUNTABILITY:

All access including key use, is time stamped, stored, and automatically updated for reporting in KnoxConnect Cloud Management Software


INTERNAL ANTENNA:


Antenna mounted inside door provides smaller footprint and easier installation





KNOX MEDVAULT® 2.75

SECURE NARCOTICS STORAGE









Models	Description	Override Options	Dimensions External	Dimensions Internal	Finish	Weight (lbs.)	Material
5540	MedVault 2.75 Large Recessed Mount	Mechanical		8.8" H X 11.3" W X 6.6" D	Textured Powder Coat		Cast Aluminum
KLS-5540	KnoxLock™ MedVault 2.75 Large Recessed Mount	eKey	10.8" H X 14.1" W X 10" D			19.1	
5541	MedVault 2.75 Large Surface Mount	Mechanical	9.25" H X 12.6" W X 10" D			17.2	
KLS-5541	KnoxLock™ MedVault 2.75 Large Surface Mount	eKey					
MEDVAULT M	IINI MECHANICAL SPECIFICATION	s					
5240	MedVault 2.75 Mini Recessed Mount	Mechanical			Textured	9.7	Cast
KLS-5240	KnoxLock™ MedVault 2.75 Mini Recessed Mount	eKey	8.3" H X 10.3" W X 6.6" D	6.011.1.7.6.711.147.4.511.5			
5241	MedVault 2.75 Mini Surface Mount	Mechanical		- 6.0" H X 6.7" W X 4.5" D	Powder Coat		Aluminur
KLS-5241	KnoxLock ™ MedVault 2.75 Mini Surface Mount	eKey	6.8" H X 9.0" W X 6.4" D			9.1	
ELECTRICAL	SPECIFICATIONS						
Operating Temp	-20°C to 65°C (-4°F to 149°F)		Wiring	14-16 AWG			
Humidity	95% RTH@ 25 C 76 hours		Communication	Ethernet or Wi-Fi			
Memory	Up to 16,000 audit events		Programming	USB 2.0 A Male to USB-C			
Memory	Up to 5,000 PIN		Networking				
Power Input	11.3 to 15.5 VDC		Ethernet	802.3 u			
Standby Current	400 mA		Wi-Fi	802.11 b/g/n (2.4 Ghz)			
Peak Current	3 Amps Regulatory						
Battery	CR2450 Lithium		UL	437 (Lock Core)			
			FCC/IC	Part 15 A			
ACCESSORIE	S & REPAIR PARTS						1
91178	Replacement USB-A to USB-C Programming Cable						3
91196	MedVault 2.75 Bolt Mount Antenna Kit						
91197	MedVault 2.75 Magnetic Mount Antenna Kit				Ad.		
91198	MedVault 2.75 Tech Lock Package*					1	
91199	MedVault 2.75 SMA Connector						
91203	MedVault 2.75 Power Cable			66			
91204	MedVault 2.75 AC Adapter			E	, 3		
91206	Adapter, RP-SMA 90 Degree						

^{*}MedVault 2.75 does not include tech lock. The tech lock can be purchased separately.

ABOUT THE KNOX COMPANY

Since 1975, the Knox Company has successfully developed innovative rapid access solutions for first responders with products that provide fast, safe, and secure entry into commercial, industrial, and residential properties, while minimizing damage and maximizing safety. Today, more than 15,000 fire, EMS, and law enforcement departments/agencies depend on Knox products to gain access into over one million buildings/properties.